

# Source Code Highlight Filter

REVISION HISTORY
------------------

NUMBER	DATE	DESCRIPTION	NAME
8.4.3	13 April 2009		

## Contents

<b>1</b>	<b>Examples</b>	<b>1</b>
1.1	Source code paragraphs . . . . .	1
1.2	Unnumbered source code listing . . . . .	1
1.3	Numbered source code listing with callouts . . . . .	2
<b>2</b>	<b>Installation</b>	<b>3</b>
2.1	HTML . . . . .	3
2.2	DocBook . . . . .	3
2.3	Testing . . . . .	3

---

The *AsciiDoc* distribution includes a source code syntax highlight filter (`source-highlight-filter.conf`). It uses **GNU source-highlight** to highlight HTML outputs; DocBook outputs are highlighted by toolchains that have `programlisting` element highlight support, for example *dblatex*.

---

#### Tip

If the source *language* attribute has been set (using an *AttributeEntry* or from the command-line) you don't have to specify it in each source code block.

---

## 1 Examples

### 1.1 Source code paragraphs

The `source` paragraph style will highlight a paragraph of source code. These three code paragraphs:

```
[source,python]
if n < 0: print 'Hello World!'

:language: python

[source]
if n < 0: print 'Hello World!'

[source,ruby,numbered]
[true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
  puts "#{a.inspect} => #{b.inspect}"
```

Render this highlighted source code:

```
if n < 0: print 'Hello World!'
```

```
if n < 0: print 'Hello World!'
```

```
1 [true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
2   puts "#{a.inspect} => #{b.inspect}"
```

### 1.2 Unnumbered source code listing

This `source-highlight` filtered block:

```
[source,python]
-----
''' A multi-line
    comment.'''
def sub_word(mo):
    ''' Single line comment.'''
    word = mo.group('word')    # Inline comment
    if word in keywords[language]:
        return quote + word + quote
    else:
        return word
-----
```

Renders this highlighted source code:

---

```
''' A multi-line
comment.'''
def sub_word(mo):
    ''' Single line comment.'''
    word = mo.group('word')      # Inline comment
    if word in keywords[language]:
        return quote + word + quote
    else:
        return word
```

### 1.3 Numbered source code listing with callouts

This source-highlight filtered block:

```
[source,ruby,numbered]
-----
#
# Useful Ruby base class extensions.
#

class Array

  # Execute a block passing it corresponding items in
  # +self+ and +other_array+.
  # If self has less items than other_array it is repeated.

  def cycle(other_array) # :yields: item, other_item
    other_array.each_with_index do |item, index|
      yield(self[index % self.length], item)
    end
  end

end

if $0 == __FILE__                                     <1>
  # Array#cycle test
  # true => 0
  # false => 1
  # true => 2
  # false => 3
  # true => 4
  puts 'Array#cycle test'                               <2>
  [true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
    puts "#{a.inspect} => #{b.inspect}"
  end
end
-----

<1> First callout.
<2> Second callout.
```

Renders this highlighted source code:

```
1 #
2 # Useful Ruby base class extensions.
3 #
4
5 class Array
6
7   # Execute a block passing it corresponding items in
```

```
8  # +self+ and +other_array+.
9  # If self has less items than other_array it is repeated.
10
11  def cycle(other_array) # :yields: item, other_item
12    other_array.each_with_index do |item, index|
13      yield(self[index % self.length], item)
14    end
15  end
16
17 end
18
19 if $0 == __FILE__ ❶
20   # Array#cycle test
21   # true => 0
22   # false => 1
23   # true => 2
24   # false => 3
25   # true => 4
26   puts 'Array#cycle test' ❷
27   [true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
28     puts "#{a.inspect} => #{b.inspect}"
29   end
30 end
```

- ❶ First callout.
- ❷ Second callout.

## 2 Installation

### 2.1 HTML

If you want to syntax highlight *AsciiDoc* HTML outputs (html4 and xhtml11 backends) you need to install [GNU source-highlight](#) (most distributions have this package).

### 2.2 DocBook

*AsciiDoc* encloses the source code in a DocBook *programlisting* element and leaves source code highlighting to the DocBook toolchain (d<sub>o</sub>blatex has a particularly nice programlisting highlighter). The DocBook programlisting element is assigned two attributes:

1. The *language* attribute is set to the *AsciiDoc language* attribute.
2. The *linenumbers* attribute is set to the *AsciiDoc src\_numbered* attribute (*numbered* or *unnumbered*).

### 2.3 Testing

Test the filter by converting the test file to HTML with *AsciiDoc*:

```
$ asciidoc -v ./filters/source/source-highlight-filter-test.txt
$ firefox ./filters/source/source-highlight-filter-test.html &
```